

Laser Range Finders

Compact Laser Range Finders

Laser Range Finder monoculars provide instant distance measurements consistently and accurately. The outstanding optics provide a sharp and clear image under all conditions.

Designed with an eye safe CE approved laser; with automatic power off for energy saving, it gives a clear digital distance indication at the press of a button.

By selecting "RAIN" mode, the distance can be measured without any influence in rainy conditions. By selecting >150 mode, the influence of the objects such as overhead electric cables and tree branches affect can be eliminated.

The range finder can be used for distance measuring in hunting, playing golf, construction and site survey.

Spec.	Models	LRF 400 (RF5400)	LRF 600 (RF5600)	LRF 600 Pro (RF5605)	LRF 1000 (RF6000)
Distance		5m-400m	5m-600m	5m-600m	15m-999m
Magnification Power		6x	6x	6x	8x
Objective Lens Diameter (mm)		25	25	25	30
Type of Prism		BK7	BK7	BK7	BK7
Exit Pupil Diameter (mm)		3.8	3.8	3.8	3.6
Eye Relief(mm)		12	12	12	13
FOV (angle)		7°	7°	7°	7°
Twist-up ocular		Yes	Yes	Yes	Yes
Waterproof		No	Yes	Yes	No
Angle indication		No	No	Yes	No
Solar Power		No	No	Yes	No
FOV m / 1,000m		122m / 1000m	122m / 1000m	122m / 1000m	122m / 1000m
Unit Dimension (mm)		113 x 72 x 43	120 x 72 x 43	120 x 72 x 44.5	126 x 84 x 45
Unit Weight (g)		225g	222g	235g	266g
Battery supplied		3V CR2	3V CR2	3V CR2	3V CR2

Supplied with:

Carrying case
Neck strap
Lens cleaning cloth
User's manual



Compact LRF 400 - RF5400

400M RANGE



Compact LRF 600 - RF5600

600M RANGE



Compact LRF 600 Pro - RF5605

600M RANGE

ANGLE (+ - 90°)

SOLAR POWER*

*Rechargeable battery is internal. Alternatively a 3V CR2 can be used.



Compact LRF 1000 - RF6000

1000M RANGE

LONG DISTANCE RANGE FINDING



CODE	MODEL	FIELD OF VIEW	EYE RELIEF mm	DIMENSIONS mm	WEIGHT oz / g
RF5400	LRF 400	122m @ 1000m	12	113 x 72 x 43	7.9 / 225
RF5600	LRF 600	122m @ 1000m	12	120 x 72 x 43	7.8 / 222
RF5605	LRF 600 Pro	122m @ 1000m	12	120 x 72 x 44.5	8.3 / 235
RF6000	LRF 1000	122m @ 1000m	13	126 x 84 x 45	9.3 / 266
BA7816	Replacement CR2 3V battery	-	-	-	-